



NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING: 125 VAC RMS
- 2.CURRENT RATING: 1.5 AMP
- 3.CONTACT RESISTANCE: 100 MILLIOHS MAX
- 4.INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

MECHANICAL

- 1.HOUSING MATERIAL: PC UL 94V-O.
- 2.Contact Blade: Phosphor Bronze.
- 3.INSERT MATERIAL: FLAME RETARDANCY ABS UL94V-O.
- 4.PCB MATERIAL: FR-4 , THICKNESS 1.6MM.
- 5.CONTACT MATERIAL: PHOSPHOR BRONZE STAMP PIN T=0.35MM.
- 6.IDC CONTACT MATERIAL: PHOSPHOR BRONZE T=0.50MM, WITH TIN PLATING.
- 7.WIRE: 24AWG -26AWG.

TOLERANCE						
.X	.XX	.XXX				
.X	.015	.30	NONE	M/M	REV A	
.XX	.010	.10	UNIT	M/M		
.XXX	.005	.05	SHEET	1/1	DATE	
DRAWN BY			DATE	2013/02/22		
CHECK BY			TITLE: CAT.6A KEYSTONE JACK			
APPD BY			PART NO: KJCC6ARJ45FUBK			