



NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING : 125 VAC RMS
- 2.CURRENT RATING : 1.5 AMP
- 3.CONTACT RESISTANCE : 100 MILLIOHMS MAX
- 4.INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH : 750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1.STORAGE : -40° TO +85°
- 2.OPERATION : -30° TO 70°

MECHANICAL:

- 1.SHIELD MATERIAL : BRASS T=0.30mm NICKEL PLATING
- 2.HOUSING MATERIAL : PC UL94V-2
- 3. INSERT MATERIAL : FLAME RETARDANCY ABS UL94V-2
- 4. PCB MATERIAL : FR-4 THICKNESS:1.6mm
- 5. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN T=0.35mm
- 6. IDC CONTACT MATERIAL : PHOSPHOR BRONZE T=0.50mm NICKEL PLATING
- 7. WIRE : AWG 24-26

PIN	PIN
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8

