



# RG-223 50 Ohms Coaxial Cable

## CONSTRUCTION

Inner Conductor  
 Insulation  
 1st Outer Conductor  
 2nd Outer Conductor  
 Jacket



## PROPERTIES

**Min. Bending Radius:** 14.5 mm  
**Max. Pulling Tension** 150 N  
**Crush resistance of cable** (load of 700) < 1 %  
**Rated Temperature**  
 Storage/operating temperature -20~+75 °C  
 Outdoor Installation -20 °C

## PHYSICAL SPECIFICATIONS

**Center Conductor** Solid Silver Plated Copper  
 Conductor Dia.(+/-0.015mm) 0.90  
 Min. Break Strength (N) 300

**Insulation** Solid Polyethylene  
 Insulation Dia.(+/-0.10mm) 2.95  
 Color Neutral  
 Centricity (%) ≥ 85  
 Adhesion 5 to 25N @ 25mm

**1st Outer Conductor** Silver Plated Bare Copper Braid  
 Conductor Dia.(+/-0.01mm) 0.12  
 No. of Wires 112  
 Coverage (+/-3%) 90

**2nd Outer Conductor** Silver Plated Bare Copper Braid  
 Conductor Dia.(+/-0.01mm) 0.12  
 No. of Wires 128  
 Coverage (+/-3%) 95

**Outer Jacket** PVC  
 Outer Dia (+/-0.20mm) 5.30  
 Tensile strength ≥ 12.5 N/mm<sup>2</sup>  
 Elongation at break ≥ 150 %  
 Adhesion 150 to 250N @ 200mm

## ELECTRICAL CHARACTERISTICS

**Characteristic Impedance** 50 ±3ohm  
**Capacitance** 101 ±3pF/m  
**Velocity Ratio** > 66 %

**DC Resistance: Centre Conductor** < 28.0 ohm/km  
**DC Resistance: Outer Conductor** < 7.00 ohm/km

**Peak Power rating** 2.10 Kw  
**Cut Off Frequency** 32.00 GHz  
**Insulation Resistance** > 2,500 MΩ·km  
**Dielectric Strength** 1000 VAC  
**Voltage Withstand** 2000 VDC

**Screening Factor at 1 - 1000MHz** > 90 dB

Frequency	Attenuation (at 20 °C)
1 MHz	0.35 dB/100Ft
10 MHz	1.20 dB/100Ft
50 MHz	2.80 dB/100Ft
100 MHz	4.10 dB/100Ft
200 MHz	6.00 dB/100Ft
400 MHz	8.80 dB/100Ft
500 MHz	9.90 dB/100Ft
700 MHz	12.00 dB/100Ft
900 MHz	13.80 dB/100Ft
1000 MHz	14.50 dB/100Ft
3000 MHz	25.74 dB/100Ft